

MILLTEC

ISO 9001:2008/ ISO 14001:2004

MILLTEC ELITE SERIES



SETTING BENCHMARK FOR HIGHEST PERFORMANCE

THICK / THIN GRADER

TOLL FREE :1800-102-8431

WWW.MILLTECMACHINERY.COM

This machine is used to separate grains of non uniform thickness from brown rice or polished rice. The material is passed through revolving cylindrical screens for separating over and under sized grains. Highly efficient for separating admixture of over size or under size grains. This can also be used to separate immature grains, broken etc.



• **Features / Advantages:**

A specially designed cylindrical screen ensures accuracy of separation.

An integrated cleaning brush counter rotates with the drum to avoid choking of slots.

Customized selection of sieves to suit various application.

Can be fitted with variable speed drive (optional).

• **Technical Specifications**

Machine Type	RTGA1	RTGB1	RTGC1
Capacity Ton/hour with Precleaner	2 - 3 TON	4 - 6 TON	6 - 10 TON
Gear Motor Power HP/KW	0.50/0.37	1.0/0.735	2/1.5
Voltage (V)/Frequency (Hz)	415/50	415/50	415/50
Working RPM	189	181	181
Aspiration (CMM)	5	5	5
Weight (KG)	430	620	840
Overall size LxWxH (MM)	2188 x 870 x 1700	2188 x 870 x 2301	2188 x 870 x 2898

NOTE : Unless otherwise specified capacity (TON/HOUR) should be considered for Paddy only.

MILLTEC MACHINERY PVT. LTD.
 NO. 51/A, 1ST PHASE, KIADB INDL AREA
 BOMMASANDRA, BANGALORE -560099

Follow us on



TEL: +91-80-28016666+91-80-27831128
EMAIL: MARKETING@MILLTECMACHINERY.COM
WEBSITE : HTTP://MILLTECMACHINERY.COM
HTTP://MILLTECMACHINERY.IN